





- USB port for data download
- Independent display for refrigerator section and freezer section
- Optional remote alarm and monitor via Internet
- Drawers with divided compartments
- Shelves with divided sections
- Multiple alarms to detect malfunctions
- Multi-malfunction alarms, precautionary alarm

## **Combined Refrigerator and Freezer**

## **Excellent Performance**

- Refrigerator compartment temperature range: 2°C to 8°C
- Adjustable freezer compartment temperature range: -20°C to -40°C

Model			HYCD-282
Technical Data	Cabinet Type		Upright
	Climate Class		4
	Cooling Type		Refrigertor:Forced air cooling Freezer: Direct cooling
	Defrost Mode		Refrigerator: Auto Freezer: Manual
	Refrigerant		CFC-Free
	Sound Level (dB(A))		43
Performance	Cooling Performance(°C)		Freezer:-40
	Temp Range(°C)		2~8/-20~-40
Control	Controller		Microprocessor
	Display		LCD
Electrical Data	Power Supply(V/Hz)		220~240/50
	Power(W)		400
	Electrical Current(A)		2.8
Dimensions	Capacity(L/Cu.Ft)		Refrigerator:185/6.5 Freezer: 97/3.4
	Net/Gross Weight(approx)	(kg)	145/160
		(lbs)	320.0/352.7
	Interior Dimensions(W*D*H)	(mm)	Re frigerator: 605*510*720 Freezer: 515*465*440
		(in)	Refrigerator: 23.8*20.0*28.3 Freezer: 20.3*18.3*17.3
	Exterior Dimensions(W*D*H)	(mm)	736*660*1810
		(in)	29.0*26.0*71.3
	Packing Dimension(W*D*H)	(mm)	775*720*1930
		(in)	30.5*28.3*76
	Container Load(20'/40'/40'H)		21/45/45
Accessories	Caster		Y
	Foot		Y
	Porthole		Y
	Drawers/Inner Doors		Refrigerator: 3/1 Freezer: 0/2
	USB Interface		Y
Other	Certification		CE

Haier Medical and Laboratory Products Co., Ltd Haier industrial Park, No. 1 Haier Road, Qingdao, 266101, China









