

Combined Refrigerator and Freezer HYCD-282A





HYCD-282A



Separately Controlled Refrigerator and Freezer Combination Unit

- USB port for data download
- Capable of recording temperature data for up to one month automatically
- Independent display for refrigerator section and freezer section
- Optional remote alarm and monitor via Internet
- Drawers with divided compartments
- Shelves with divided sections
- Multiple alarms to detect malfunctions
- Multi-malfunction alarms, precautionary alarm

MEDICAL

Combined Refrigerator and Freezer

Excellent Performance

- Refrigerator compartment temperature range: 2°C to 8°C
- Adjustable freezer compartment temperature range: -20°C to -40°C

Model			HYCD-282A		
Technical Data	Cabinet Type		Upright		
	Climate Class		4		
	Cooling Type		Refrigertor:Forced air cooling Freezer: Direct cooling		
	Defrost Mode		Refrigerator: Auto Freezer: Manual		
	Refrigerant		CFC-Free		
	Sound Level (dB(A))		43		
Performance	Cooling Performance(°C)		Freezer:-40		
	Temp Range(°C)		2-8/-2040		
Control	Controller		Microprocessor		
	Display		LCD		
Electrical Data	Power Supply(V/Hz)		220~240/50	208-230/60	
	Power(W)		400	400	
	Electrical Current(A)		2.8	2.8	
Dimensions	Capacity(L/Cu.Ft)		Refrigerator:185/6.5 Freezer: 97/3.4		
	Net/Gross Weight(approx)	(kg)	14.	145/160	
		(lbs)		320.0/352.7	
	Interior Dimensions(W*D*H)	(mm)	Re frigerator: 605*510*720 Freezer: 515*465*440		
		(in)	Refrigerator: 23.8*20.0*28.3 Freezer: 20.3*18.3*17.3		
	Exterior Dimensions(W*D*H)	(mm)	736*660*1810		
		(in)	29.0*2	29.0*26.0*71.3	
	Packing Dimension(W*D*H)	(mm)	775*7	775*720*1930	
		(in)	30.5*	30.5*28.3*76	
	Container Load(20'/40'/40'H)		21/45/45		
Accessories	Caster		Y		
	Foot		Y		
	Porthole			Y	
	Drawers/Inner Doors		Refrigerator: 3	Refrigerator: 3/1 Freezer: 0/2	
	USB Interface			Y	
Other	Certification			CE	

Haier Medical and Laboratory Products Co., Ltd Haier industrial Park, No. 1 Haier Road, Qingdao, 266101, China









